



DIVISION 9 - SECTION 09 60 00.11
QTrbm Rebonded Recycled Rubber Impact Sound Insulation
PATENT PENDING

PART 1.0- GENERAL

1.1 SUMMARY

- A. The work of this section includes:
 - 1. Types of rebonded recycled rubber Impact Sound Insulation to be placed under flooring in living units.
 - 2. Adhesives
- B. Related Sections: Section(s) related to this section include:
 - 1. Concrete Substrate
 - 2. Plywood Substrate
 - 3. Tile
 - 4. Carpeting
 - 5. Noise Control and Vibration Isolation

1.2 REFERENCES

- A. Standards listed by reference, including revisions by issuing authority, form a part of this specification section to extent indicated. Standards listed are identified by issuing authority, authority abbreviation, designation number, title or other designation established by issuing authority. Standards subsequently referenced herein are referred to by issuing authority abbreviation and standard designation.
- B. American Society for Testing and Materials (ASTM):
 - 1. ASTM E492 Standard Test Method for Laboratory Measurement of Impact Sound Transmission Through Floor-Ceiling Assemblies Using the Tapping Machine
 - 2. ASTM C627 Standard Test Method for Evaluating Ceramic Floor Tile Installation Systems Using the Robinson-Type Floor Tester
 - 3. ASTM E989 Standard Classification for Determination of Impact Insulation Class (IIC)
 - 4. ASTM E1007 Standard Test Method for Field Measurement of Tapping Machine Impact Sound Transmission Through Floor-Ceiling Assemblies and Associated Support Structures
 - 5. ASTM E2179 Standard Test Method for Laboratory Measurement of the Effectiveness of Floor Coverings in Reducing Impact Sound Transmission Through Concrete Floors
 - 6. ASTM E90 Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements
 - 7. ASTM E336 Standard Test Method for Measurement of Airborne Sound Insulation in Buildings
- C. South Coast Air Quality Management District (SCAQMD) Rule #1168
 - 1. VOC standards for adhesive and sealant applications
- D. Leadership in Energy and Environmental Design – LEED®

1. International Organization for Standardization® document, ISO 14021 - Provides guidance on the terminology, symbols, testing and verification methodologies that an organization should use for self-declaration of the environmental aspects of its products and services."

1.3 SYSTEM DESCRIPTION

- A. Performance Requirements: Provide recycled rubber resilient flooring, which has been manufactured and installed to maintain performance criteria stated by manufacturer without defects, damage or failure.

1.4 SUBMITTALS

- A. General: Submit listed submittals in accordance with Conditions of the Contract and Division 1 Submittal Procedures Section.
- B. LEED: Provide documentation of how the requirements for credit will be met.
 1. List of proposed materials with recycled content. Indicate pre-consumer and post-consumer content.
 2. Product data and certification letter indicating percentage of recycled content for both pre-consumer and post-consumer content.
 3. Recycled content is defined in accordance with the International Organization for Standardization document, ISO 14021 Environmental labels and declarations.
 - a. Post-consumer material - waste materials diverted from the waste stream after consumer or commercial use.
 - b. Pre-consumer material - materials diverted from the waste stream during the manufacturing process. Excluded are regrind, rework, and scrap.
- C. Product Data: Submit product data, including manufacturer's guide specifications product sheet, for specified products.
- D. Shop Drawings: Manufacturer's specifications, catalog cuts and other items needed to demonstrate compliance with the specified requirements. Also the manufacturer's recommended installation procedures, which, when approved by the architect, will become the basis for accepting or rejecting actual installation procedures used on the work.
- E. Samples: Submit selection and verification samples for finishes, colors and textures.
- F. Quality Assurance Submittals: Submit the following:
 1. Test Reports: Certified test reports showing compliance with specified performance characteristics and physical properties.
 2. Certificates: Product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.
 3. Manufacturer's Instructions: Manufacturer's installation instructions.
- G. Closeout Submittals: Submit the following:
 1. Warranty: Warranty documents specified herein.

1.5 QUALITY ASSURANCE

- A. Qualifications:
 1. Installer Qualifications: Installer experienced in performing work of this section who has specialized in installation of work similar to that required for this project.
 - a. Certificate: When requested, submit certificate indicating qualification.
 2. Manufacturer's Qualifications: Manufacturer capable of approving application method.
- B. Regulatory Requirements: [specify applicable requirements of regulatory agencies].
- C. Mock-Ups: Install at project site a job mock-up using acceptable products and manufacturer-approved installation methods. Comply with workmanship standard. Comply with Division 1 Quality Control (Mock-Up Requirements) Section.

1. Mock-Up Size: As determined by acoustical consultant.
 2. Maintenance: Maintain mock-up during construction for workmanship comparison; remove and legally dispose of mock-up when no longer required.
 3. Incorporation: Mock-up may be incorporated into final construction upon Owner's approval.
- D. Pre-installation Meetings: Conduct pre-installation meeting to verify project requirements, substrate conditions, manufacturer's instructions and manufacturer's warranty requirements. Comply with Division 1 Project Management and Coordination (Project Meetings) Section.
- E. Pre-installation Testing: Conduct pre-installation testing as follows: [specify substrate testing; consult with flooring manufacturer].

1.6 DELIVERY, STORAGE & HANDLING

- A. General: Comply with Division 1 Product Requirements Sections.
- B. Ordering: Comply with manufacturer's ordering instructions and lead time requirements to avoid construction delays.
- C. Delivery: Deliver materials in manufacturer's original, unopened, undamaged containers with identification labels intact.
- D. Storage and Protection: Store materials at temperature and humidity conditions recommended by manufacturer and protect from exposure to harmful weather conditions.

1.7 PROJECT CONDITIONS

- A. Temperature Requirements: Maintain air temperature in spaces where products will be installed for time period before, during and after installation as recommended by manufacturer.
- B. Field Measurements: Verify actual measurements/openings by field measurements before fabrication; show recorded measurements on shop drawings. Coordinate field measurements and fabrication schedule with construction progress to avoid construction delays.

1.8 WARRANTY

- A. Project Warranty: Refer to Conditions of the Contract for project warranty provisions.
1. The recommendations for applications and installation are based on our extensive experience and on current technological practice. Our liability and responsibility in the event of damages are limited to the extent defined in our General Terms and Conditions of Business and are not in any way increased by the above recommendations or by advice given by our sales representatives or applications engineering staff.
 2. ECORE International™ is a corporation duly organized and validly existing under the laws of the Commonwealth of Pennsylvania. ECORE offers a limited lifetime warranty on the QT brand of Impact Sound Insulation products against defects in material and workmanship and that QT shall meet all published specifications and shall perform effectively. ECORE warrants that during the warranty period that QT shall not harden, become brittle, chip, crack, tear or exhibit any signs of excessive deterioration except for normal wear and tear. All other warranties including implied warranties for a particular purpose are expressly excluded. The sole remedy against the seller will be the replacement or repair of the defective goods, or at seller's option, credit may be issued not exceeding the selling price of the defective goods.

1.9 MAINTENANCE

- A. Extra Materials: Deliver to Owner extra materials from same production run as products installed. Package products with protective covering and identify with descriptive labels. Comply with Division 1 Closeout Submittals (Maintenance Materials) Section.
1. Quantity: Furnish quantity of rebonded recycled rubber Impact Sound Insulation units as requested on purchase order.
 2. Delivery, Storage and Protection: Comply with Owner's requirements for delivery, storage and protection of extra materials.

PART 2.0 - PROPRIETARY MANUFACTURER/PRODUCTS

2.1 MANUFACTURER: ECORE International

- A. Address: 715 Fountain Ave., Lancaster, PA 17601; Telephone: (800) 322-1923, (717) 295-3400; Fax: (717) 295-3414; Email: info@ecoreintl.com

2.2 PROPRIETARY PRODUCT(S)

- A. QT™ Rebonded Recycled Rubber Impact Sound Insulation and Adhesives manufactured by ECORE.
1. QTrbm Rebonded Recycled Rubber [sheet] Underlayment
 2. QT Rebonded Recycled Rubber Perimeter Isolation Strip
 3. E-Grip™ II a one-component polyurethane adhesive

2.3.1 QTrbm Rebonded Recycled Rubber [sheet] Impact Sound Insulation Underlayment

- A. Product Name: The non-laminated, single-ply rebonded rubber underlayment furnished under this specification shall be ECORE's QTrbm Rebonded Recycled Rubber Impact Sound Insulation Underlayment.
- B. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber. QTrbm is a dimpled, resilient base mat that can be applied under gypsum or full weight concrete to produce some of the thinnest sound rated systems in the industry.
- C. PATENT No.: PATENT PENDING
- D. Sheet Dimension: QTrbm rolled rubber underlayment will have an overall thickness of _____(specify: 1/4" [6 mm] standard in 4.5' by 30' [1.4 m by 9.1 m] roll size or 3/8" [10 mm] standard in 4.5' by 30' [1.4 m by 9.1 m] roll size or 3/4" [17 mm] standard in 4.5' by 30' [1.4 m by 9.1 m] roll size) or 1" [25 mm] standard in 4' by 30' [1.2 m by 9.1 m] roll size).
- E. Sheet Weight: 0.6 lb/ft² [2.8 kg/m²], 1.0 lb/ft² [5.1 kg/m²], 1.3 lb/ft² [6.3 kg/m²], 1.6 lb/ft² [7.9 kg/m²]
- F. Sheet Standard Tolerances: Roll width: + 3/4" - 0"
Roll length: +1% - 0"
Thickness: ±0.3 mm
- G. Laboratory Impact Insulation Class: Specified floor-ceiling assembly must be tested in a NVLAP certified laboratory and comply with ASTM standards (ASTM E492)
- H. Field Impact Insulation Class: Floor-ceiling assembly must meet requirement as stated by building code and/or acoustical consultant (ASTM E1007)
- I. Shall be ICC-ES certified
- J. Shall be UL listed
- K. VOC Washington State IAQ Test: pass (ASTM D5116)

2.3.2 QT Rebonded Recycled Rubber Perimeter Isolation Strip

- | | |
|---------------------|---|
| A. Product Name: | The non-laminated, single-ply rebonded rubber perimeter isolation strip under this specification shall be ECORE's Rebonded Recycled Rubber Perimeter Isolation Strip. |
| B. Material: | Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber. QT Perimeter Isolation Strip is a flat, resilient strip that is used to build a tub around the floor so that no hard surface (floor covering) touches any hard vertical surface (protrusion or wall). |
| C. Sheet Dimension: | QT's rolled perimeter isolation strip will have an overall thickness of 1/4" [5 mm] in 3" by 30' [76 mm by 9144 mm] roll size. |
| D. Sheet Weight: | 0.74 lb/ft ² [3.6 kg/m ²] |

2.3.3 E-Grip™ II one-component polyurethane adhesive

- | | |
|---|---|
| A. Product Name: | The one-part urethane adhesive under this specification shall be ECORE's E-Grip™ II one-component polyurethane adhesive. |
| B. Material: | E-Grip II is a one-component polyurethane moisture cured, non-sag, permanently elastic adhesive that has excellent adhesion to elastomers, concrete and wood and is engineered for indoor and outdoor applications. |
| C. Adhesive Type: | one-component polyurethane |
| D. Adhesive Cure System: | moisture cured |
| E. Weight: | 5 gallon pail-60 lbs
2-1/2 gallon pail-31 lbs |
| F. Color: | medium grey |
| G. VOC Content: | 0.29 lb/gal (34 g/L) |
| H. Freeze/Thaw: | stable |
| I. Application Temperature: | 40° F - 100° F |
| J. Calcium Chloride Test:
(ASTM F1869) | Maximum 5.5 lbs per 1,000 sq. ft. in 24 hrs. |
| K. Flashpoint: | > 200° F |
| L. Shelf Life: | 6 months |
| M. Working Time: | 30-40 minutes |
| N. Trowel: | 1/16" square notched trowel ⁽¹⁾ |
| O. Coverage Rate: | 95 ft ² per gallon (1/16" square notched trowel) |
| P. SCAQMD Rule #1168 | .29 lb./gal. |

(1) For indoor installation on concrete or plywood subfloors only.
See QT Installation Manual for instructions.

2.4 PRODUCT SUBSTITUTIONS

- A. Substitutions: No substitutions permitted.

2.5 RELATED MATERIALS

- A. Related Materials: Refer to other sections listed in Related Sections paragraph herein for related materials.

2.6 SOURCE QUALITY

- A. Source Quality: Obtain rebonded recycled rubber impact sound insulation materials from a single manufacturer.

PART 3.0 - EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- A. Compliance: Comply with manufacturer's product data, including product technical bulletins, product catalog installation instructions and product carton instructions for installation.

3.2 EXAMINATION

- A. Site Verification of Conditions: Verify substrate conditions, which have been previously installed under other sections, are acceptable for product installation in accordance with manufacturer's instructions.

3.3 PREPARATION

- A. Surface Preparation: Surfaces shall be prepared in accordance with ANSI standards.

3.4 ERECTION/INSTALLATION/APPLICATION/CONSTRUCTION

- A. Rebonded Recycled Rubber Impact Sound Insulation: Comply with the QT technical manual for procedures and techniques for rebonded recycled rubber Impact Sound Insulation installation.
- B. Related Products Installation: Refer to other sections listed in Related Sections paragraph herein for related products installation.
- C. Installation should not begin until all other trades are finished in the area.
- D. Areas to receive the rebonded recycled rubber Impact Sound Insulation should be weather tight and maintained at a minimum uniform temperature of 65°F (18°C) for 48 hours before, during and after the installation.

3.5 FIELD QUALITY REQUIREMENTS

- A. Manufacturer's Field Services: Upon Owner's request, provide manufacturer's field service consisting of product use recommendations in accordance with manufacturer's instructions.
- B. Field Tests should be performed by an independent acoustical laboratory accredited by the U.S. Department of Commerce, National Institute of Standards and Technology under the National Voluntary Laboratory Accreditation Program for the specified test procedure.
- C. The cost for all field acoustical testing, corrective work associated with the installation of the rebonded recycled rubber Impact Sound Insulation and flooring to meet the minimum requirements, shall be borne by the flooring contractor(s).

3.6 CLEANING

- A. Remove temporary coverings and protection of adjacent work areas. Repair or replace damaged installed products. Clean installed products in accordance with manufacturer's instructions prior to Owner's acceptance. Remove construction debris from project site and legally dispose of debris.

3.7 PROTECTION

- A. Protection: Protect installed product and finish surfaces from damage during construction.

3.8 SCHEDULES

- A. Schedules: [Specify reference to applicable schedules].

END OF SECTION

©2007 All designs, text, and colors are copyrighted by ECORE Intl. QT is a trademark of ECORE Intl. QTrbm patent pending. LEED is a registered trademark of the U.S. Green Building Council. International Organization of Standardization is a registered trademark of ISO.