


Adhesives Product Sales Sheet

Product	Available In	Type	Works With	Maximum RH (per ASTM F-2170)	Substrate pH	Flash Time	Working Time	Shelf Life	Freeze/ Thaw Stability	Antimicrobial	Trowel	Spread Rate
 E-Grip III	4 Gallon Pail	One-Part Urethane	Vulcanized Composition Rubber	85%	7-9	None	30-45 minutes	1 Year	Stable	Yes	1/16" x 1/32" x 1/32" U-notch	140 SF/gal
	10.1 oz Cartridge*										1/16" sq. notch	95 SF/gal
											1/8" sq. notch	60 SF/gal
 E-Grip 95	4 Gallon Pail	One-Part Urethane	Vulcanized Composition Rubber	95%	Max of 12	None	30-45 minutes	1 Year	Stable	Yes	1/16" x 1/32" x 1/32" U-notch	160 SF/gal
											1/16" sq. notch	115 SF/gal
 E-Grip 99	4 Gallon Pail	One-Part Modified Urethane	Vulcanized Composition Rubber Vinyl and LVT over Concrete (not over rubber)	99%	5 to 14	LVT: 10-15 minutes All other products: None	45 minutes	1 Year	Stable to 10°F (-12°C)	Yes	1/16" x 1/32" x 1/32" U-notch (LVT/LVP only)	135 SF/gal
											1/16" sq. notch	105 SF/gal
 E-Grip Tape	29" x 131' Roll	Tape	Products under 8.5mm	80%	7-9	N/A	N/A	2 years from Ecore ship date	N/A	No	N/A	322 SF/roll

* One 10.1 oz cartridge of E-Grip III is required for every 15 Quad Blok (1" Tiles) or for every 10 Quad Bloks (2.5" Tiles)

Adhesive Comparison Matrix

	E-Grip III	E-Grip 95	E-Grip 99	E-Grip Tape
ph and RH	★☆☆	★★☆	★★★	★☆☆
Trowelable	★☆☆	★★★	★★★	N/A
Weighting of Seams (★☆☆ = seams need weighted)	★★☆	★☆☆	★☆☆	★★★
Open Time	★★★	★★★	★★★	N/A
Working Time	★★☆	★★☆	★★☆	N/A
Initial "Green" Strength	★★☆	★☆☆	★☆☆	★★★
Light Foot Traffic (24 Hours)	★★★	★★★	★★★	★★★ Immediately
Heavy Foot Traffic (48 Hours)	★★★	★★★	★★★	★★★ Immediately
Heavy Rolling Loads (72 Hours)	★★★	★★★	★★★	★★★ Immediately